

LS9000 MID: NON-CONTACT LENGTH & SPEED MEASUREMENT SYSTEM



Intelligent, compact non-contact linear encoder with highest accuracy in accordance with European Directive MID

A breakthrough in electro-optics design enables the LaserSpeed® 9000 MID series encoder to produce highly accurate, reliable non-contact length and speed measurements. Coupled with the Beta LaserMike DataPro 1000 MID display, the LaserSpeed 9000 MID system is certified according to the high standards of the European Measuring Instruments Directive (MID). This approval has been granted by the National Measurement Office (NMO) in 2008 under the control number UK/0126/0023.

The LaserSpeed series encoders have no moving parts, use 100% solid-state digital technology, and are permanently calibrated resulting in significant time and money savings. An integrated and enhanced version of autocorrelation, along with an Acousto-Optical modulator, gives the LaserSpeed 9000 series the capability to measure forward and reverse directions and zero speed (no motion). All LaserSpeed series encoders deliver better than $\pm 0.05\%$ accuracy to meet the Class 1 status of the EU Directive ($\pm 0.125\%$).

The MID policy was agreed upon in April 2004 and covers a number of measuring instrument types, including gas and electricity meters, petrol pumps, and automatic weighing instruments. The primary aim of the Directive is to create a single market in measuring instruments for the benefit of manufacturers and ultimately consumers across Europe.

In November 2016, the revised EC Directive 2004/22/EC from October 2006 will be in place. From this date forward, only MID-certified systems will be accepted. Older systems, such as devices with no measurement traceability or ones that have been in long-term storage, will no longer be valid. The LaserSpeed 9000 MID system meets all EU requirements. It is an ideal replacement for mechanical-type encoders (tachometers) that can lose contact on product surfaces due to slippage, vibration, and debris build-up and provide erroneous measurements, and cause damage to material. Our Accredited Customer Services offer installation support for LaserSpeed 9000 MID systems and provide effective communication with the certifying authorities to simplify the transition process.



2004/22/EG
Standard

Benefits

- ▶ High accuracy and repeatability
- ▶ Direct replacement for tachometers
- ▶ No moving parts to wear out
- ▶ Permanently calibrated
- ▶ Low cost of ownership
- ▶ Measures forward and reverse directions and zero speed (no motion)
- ▶ Provides long-term data storage with traceability of measured values
- ▶ Non-contact length and speed measurement
 - No slippage
 - Not affected by material surface or color
 - Non-marking

Range of Applications

LaserSpeed gauges are well suited for a range of applications, including, but not limited to, measuring length and speed of:

- ▶ Wire, cable, and optical cable
- ▶ Rubber tube and hose
- ▶ Paper and corrugated products
- ▶ Plastic pipe and tube
- ▶ Web products
- ▶ Plastic films and tapes
- ▶ Non-woven products
- ▶ Building materials

Accessories

- ▶ **Guide Rollers/Height Stand**
Various guides and height stand options are available for standard applications.

- ▶ **Laser Safety Enclosure**
Protects operators from direct or indirect laser beam exposure. Meets the EU laser safety requirements.



LS9000-3XX MID	-303	-306
Standoff Distance	300 mm (12 in.)	600 mm (24 in.)
Speed Range	0 to ±2000 m/min (0..±6,560 ft/min)	0 to ±2000 m/min (0..±6,560 ft/min)
Measurement Depth of Field	35 mm (1.4 in.)	50 mm (2 in.)



LS9000-3 MID (Continuous Length/Speed Measurement)

Accuracy	±0.125% of reading (instrument accuracy better than ±0.05%)	Controller Power	- 120/240 @ 4 Amp (including Gauge)
Repeatability	+/-0.02%	Spot Size	- 3 x 5 mm
Measurement Rate	>20000/s	Gauge Size	203 X 159 X 95.2 mm (8.0 X 6.3 X 3.75 in.)
Acceleration Rate	>500 m/s ²	Gauge Weight	3.4 kg (7.5 lbs)
Status via Serial I/O (Gauge)	- Laser at Temperature - Laser On - Shutter Open - Valid Measurements	Ambient Temperature	5 to 40°C (41 to 104°F) Cooling/heating is required for temperatures outside this range
Serial I/O (Controller) Data Available	- RS-232 , Ethernet - Length, Length Report - USB Printer port	Relative Humidity	Non-condensing 65%
Serial Baud Rate	- 1200, 2400, 4800, 9600, 19.2K	Degree of Protection	IP67 (Gauge) IP54 (Controller)
Status via Serial I/O (Controller)	- Length - Date - Time	Units of Measure	- m/min

Specifications are subject to change without notice.

Inputs

Input	Description	Details
1	End of Reel Report	Prints the Date, Time & current length to the USB printer port
2	Transmit Length	Outputs the Date, Time & current length over RS-232
3	Transmit Length Report	Outputs the Date, Time, Machine Number, Product Number & current length over RS-232
4	Transmit Stored Data	Transmit the stored flash memory data (last 90 days) over the EtherNet port
5	Length Reset	Resets the current length

Outputs

Control Output Type	Length Measurement Mode			
	Relay 1	Relay 2	Relay 3	Relay 4
Relay Closure	Preset Length Reached	-Preset Length Approach	Quality Factor Warning	Quality Factor Reject

This unit is a class 3B laser product and Complies with EN60825-1:2001. Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated July 26, 2001.



The following safety features required to comply with the Bureau of Radiological Health Class IIIB laser requirements are included:

- Key-operated power switch on optional controller
- Laser indicator light on supply and laser
- Delayed laser startup-laser indicator light on prior to laser radiation
- Laser beam blocking device
- Interlock capability for remote shut-off

NDC Technologies is represented in over 60 countries worldwide. ISO9001:2008 www.ndc.com/betalasermike

a **spectris** company

NDC Technologies Inc.
Tel: +1 626 960 3300
Email: info@ndc.com

NDC Technologies sa
Tel: +32 4 239 90 10
Email: sales@ndcinfrared.be

NDC China
Tel: +86 20 2887 3860
Email: info@ndcinfrared.com.cn

NDC Germany
Tel: +49 1801 977112
Email: ndcgermany@ndc.com

NDC Singapore
Tel: +65 91994120
Email: apacsales@ndc.com

NDC Technologies Ltd
Tel: +44 1621 852244
Email: enquiries@ndc.com

NDC Beta LaserMike
Tel: +1 937 233 9953
Email: sales@betalasermike.com

NDC Japan
Tel: +81 3 3255 8157
Email: ndcjapan@ndc.com

NDC Italy
Tel: +39 0331 454 207
Email: ndcitaly@ndc.com

NDC India
Tel: +91 9890800697
Email: ndcindia@ndc.com

In line with its policy of continuous improvement, NDC reserves the right to revise or replace its products or services without prior notice. The information contained in this document may not represent the latest specification and is for indicative purposes only.

Date of Issue: February 2015
© NDC Technologies 2015

Measured by Commitment

BETA LaserMike